

Express Mail Label No.: EL485651558US

Date of Deposit: January 4, 2001

Atty Docket No. 01 P 7402 US

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

This is a U.S. Patent Application for:

**TITLE:        SYSTEM AND METHOD FOR SYNCHRONIZING TWO MASTER  
                 SYSTEMS TO ONE SLAVE SYSTEM**

Inventor #1: Juergen Kockmann  
Address:     Albrecht-Duerer-Strasse 16, 40489 Duesseldorf, Germany  
Citizenship: Germany

Inventor #2: Olaf Dicker  
Address:     Eberstrasse 1, 45459 Rees, Germany  
Citizenship: Germany

# SYSTEM AND METHOD FOR SYNCHRONIZING TWO MASTER SYSTEMS TO ONE SLAVE SYSTEM

## BACKGROUND OF THE INVENTION

5

### FIELD OF THE INVENTION

The present invention relates to telecommunication systems and, particularly, to a cordless telephone system in which multiple mobile units function as system masters.

10

### DESCRIPTION OF THE RELATED ART

Cordless telephone systems are becoming increasingly popular. Such systems are advantageous in that users are freed from the constraints of a wired telephone jack. Because of the desire for multiple extensions, advanced cordless systems employing multiple handsets with a single base station have been developed. However, such systems are relatively expensive.

Relatively inexpensive conventional basic cordless telephone systems employ a single base station unit, also referred to as a fixed part, and a single handset unit, also referred to as a mobile station or portable part. In such systems, the mobile unit is defined as system master, and the base station is defined as the system slave. This is done so as to save battery power in the handsets and thereby achieve better standby times. However, such systems are incapable of supporting more than one handset per base station, thereby limiting the ability to expand the system as usage demands.

25

Operation of such a system is described with reference to FIG. 1.

Shown are a base station 102 and a handset 104. The base station 102 functions as system slave and the handset 104 functions as system master. If there is no connection between the handset 104 and the base station 102, the system is in idle mode. In this mode, the base station 102 listens continuously. The handset 104 polls the base station 102 periodically (for example, every 2000 milliseconds) by sending a transmit slot to the base station 102. The base station 102 responds with an acknowledge slot back to the handset 104. The acknowledge may also include additional status, etc.,

slots. After that, the handset 104 switches off again and will wake up after the next 2000 milliseconds.

In the idle state, the base station 102 will always find a handset because the base station 102 is the slave of the system. The slave can  
5 always synchronize to the timing of the master. Even if the master changes the timing during the time it was switched off, the slave can resynchronize the next time it receives the poll slot from the master. During an active connection, the base station will stay synchronized to the handset timing.

In a conventional systems, only one handset may be provided because  
10 more than one handset cannot be allowed to poll the base station at the same time. As such, there is a need for an ability to expand a basic cordless telephone system.

### SUMMARY OF THE INVENTION

15 These and other problems in the prior art are overcome in large part by a system and method according to the present invention. A cordless telephone system employing a base station as slave and a plurality of handsets as masters is provided. The handsets periodically poll the base station. The base station responds with acknowledge slots and also timing  
20 information whereby the handsets can adjust their poll timing so as avoid interfering with one another. If an active connection is set up between the base station and a handset, the other handset is not allowed to poll during the connection, effectively functioning as a system slave for the duration of the connection. Thus, the second handset stays synchronized to the first  
25 handset and listens until the connection is completed, whereupon it resumes normal functioning.

A base station according to an implementation of the present invention maintains a timing record and stays aware of when particular handsets will be polling. The base station is able to transmit poll responses to the handsets  
30 indicating that the handsets should adjust their poll timing so as to avoid conflicting with other handsets in the system. Correspondingly, handsets according to implementations of the present invention are able to adjust their

poll timing responsive to signaling from the base station.

The base station is further capable of transmitting poll response signals to a handset as it is about to set up an active connection with the other handset. The signal advises the other handset to turn off its polling

5 functionality, and listen for the other handset.

### BRIEF DESCRIPTION OF THE DRAWINGS

A better understanding of the invention is obtained when the following detailed description is considered in conjunction with the following drawings in  
10 which:

FIG. 1 is a block diagram of a prior art conventional cordless telephone system;

FIG. 2 is a block diagram of a cordless telephone system according to an implementation of the present invention;

15 FIG. 3 is a signaling diagram of an implementation of the present invention; and

FIG. 4 is a signaling diagram of an implementation of the present invention

### DETAILED DESCRIPTION OF THE INVENTION

20 FIGS. 2- 4 illustrate a telecommunications system including telecommunications devices according to an implementation of the present invention. A cordless telephone system employing a base station as slave and a plurality of handsets as masters is provided. The handsets periodically  
25 poll the base station. The base station responds with acknowledge slots and also timing information whereby the handsets can adjust their poll timing so as avoid interfering with one another. If an active connection is set up between the base station and a handset, the other handset is not allowed to poll during the connection, effectively functioning as a system slave for the  
30 duration of the connection. Thus, the second handset stays synchronized to the first handset and listens until the connection is completed, whereupon it resumes normal functioning.

Turning now to the drawings and, with particular attention to FIG. 2, a block diagram of an exemplary cordless telephone system is shown therein and generally identified by the reference numeral 200. The cordless telephone system 200 includes a base station or fixed part 202, and a  
5 plurality of handsets or portable parts 204a, 204b. It is noted that, while two handsets 204a, 204b are shown, a greater number may be provided. Thus, the figures are exemplary only.

The base station 202 includes a control unit (CU) 206, a telephone network interface (TNI) 208, a timer record (TRU) 210, and a transceiver  
10 (TX/RX) 212. The telephone network interface 208 typically interfaces to the public switched telephone network (PSTN) or integrated services digital network (ISDN), coupling to a private branch exchange (PBX) (not shown) or a central office (CO) (not shown). The transceiver 212 transmits and receives radio signals with the handsets 204a, 204b.

15 The control unit 206 may be implemented as software or firmware executable by one or more processors, such as microprocessors, microcontrollers, digital signal processors, or application specific integrated circuits (ASIC), as well as associated memory. The control unit 206 supervises the base station's functions and interfaces with the timer record  
20 210, as will be explained in greater detail below. More particularly, the control unit 206 receives signaling from the transceiver 212 and the network interface 208, and sets up incoming and outgoing calls. Further, the control unit 206 receives the polling transmit slots from the handsets 204a, 204b, notes their timing in the timing record 210, and responds with appropriate acknowledge  
25 polling slots. The acknowledge polling slots may include instructions to one or more of the handsets to adjust their poll timing, if the control unit 206 determines that interference is likely. The acknowledge polling slots may include an actual time by which the next polling should be delayed or the time the next polling should occur, or may only instruct the handset to execute one  
30 or more predetermined default delays or timings. Further, prior to setting up a call with one handset, the base station 202 responds to poll slots from the other handset 204 by sending signals instructing that other handset to turn off

its polling functionality.

The handsets 204a, 204b include transceivers (TX/RX) 214a, 214b, controllers (CU) 216a, 216b, and timers (TU) 218a, 218b, respectively. The transceivers 214a, 214b interface with the transceiver 212 of the base station 202, and with one another.

The controllers 216a, 216b issue polling transmit slots to the base station 202 periodically, on a time basis set by the timers 218a, 218b. Correspondingly, the controllers 216a, 216b receive acknowledge transmit slots from the base station 202 in response. Then, if necessary, they adjust their poll timers 218a, 218b such that the next polling does not interfere with that of the other handset(s). Further, if a handset, for example, handset 204a sets up a connection with the base station 202, the other handset 204b deactivates its polling functionality and synchronizes to the other handset. Then, when the call is over, the handset 204b resumes its polling. The controllers 216a, 216b may be implemented as software or firmware executable by one or more processors, such as microprocessors, microcontrollers, digital signal processors, or application specific integrated circuits (ASIC) as well as associated memory.

Turning now to FIG. 3, a diagram illustrating signal flow according to one implementation of the invention is shown. The signaling may be implemented, for example, by the respective controllers and transceivers of the handsets and base station. Prior to operation, the base station 202 and, in particular, the control unit 206 is initialized with the timing durations and the duration of responses for each of the handsets.

Initially, the handset 204a and, in particular, the controller 216a, sends a poll request PR1 to the base station 202. The base station 202 receives the poll request at its control unit 206, records the time in the timing record 210, and responds with a poll acknowledge PA1. The handset 204b's controller 216b also issues a poll request PR2 to the base station 202 at a later time. According to their internal timers 218a, 218b, the handset 204a and 204b are scheduled to issue their next poll requests at times T1 and T2, respectively. As illustrated by the dashed arrows, the resulting PR3 and PR4

5

10

20

25

30

its polling and sends a poll request PR3a to the base station 202. The poll request is also received by the handset 204b. In response, the base station 202 issues a standard poll acknowledge PA3a. The handset 204b then knows that it can resume its polling functionality, as shown by the PR4a-PA4a exchange. It is noted that, in alternate embodiments, the base station 202 may directly send a resume polling signal to the handset 204b. In either case, the method described above with reference to FIG. 3 would continue to be implemented.

The invention described in the above detailed description is not intended to be limited to the specific form set forth herein, but is intended to cover such alternatives, modifications and equivalents as can reasonably be included within the spirit and scope of the appended claims.